

Peerless

D27TG35-06

TWEETER


Fabric Diaphragm

Ferrofluid Filled Motor

High Power and Thermal Handling

High Sensitivity

Faceplate




SPECIFICATIONS

Transducer Size	1	in
Impedance	6	Ω
Frequency Range ¹	1500 - 20000	Hz
Sensitivity ² (2.83V 1W @ 1m)	91.8 90.6	dB
Power Rating (IEC 268-5)	15	W
Voice Coil Size	25.8	mm
Air Gap Winding Height	H _{ag} H _{vc}	2.5 1.7 mm
Net Weight	0.51	kg

PARAMETERS ³

Eff. Piston Area	S _d	7.07	cm ²
DC Resistance	R _e	4.9	Ω
Minimum Impedance	Z _{min}	5.4	Ω
Inductance	L _e	0.039	mH
Resonance Frequency ⁴	F _s	900	Hz
Mechanical Q Factor	Q _{ms}	1.13	-
Electrical Q Factor	Q _{es}	1.03	-
Total Q Factor	Q _{ts}	0.54	-
Moving Mass	M _{ms}	0.299	g
Compliance	C _{ms}	100	$\mu\text{m/N}$
Equivalent Volume	V _{as}	0.007	L
Motor Force Factor	Bl	2.83	Tm
Motor Efficiency	β	1.64	(Bl) ² / R _e
Linear Excursion ⁵	X _{max}	0.967	mm



Highcharts.com

Details on this spec sheet are for reference only and should not be used for setting production limits. Specifications and product cosmetics are subject to change without notice. Peerless is a registered trademark of Tymphany Enterprises. All measurements conducted in test lab at 25°C ±10°C, 50%RH ±10%. ¹ Specified by Engineering as linear working range of transducer. ² Measured at 2.83V at 1m and normalized to 1W with respect to nominal impedance. ³ Measured in Free Air without preconditioning, therefore subject to some deviation. ⁴ Impedance and F_s value measured under different conditions. ⁵ Equal/Overhung: (H_{vc} - H_{ag})/2 + H_{ag}/3. Underhung: (H_{ag} - H_{vc})/2 + H_{vc}/3. ⁶ Mechanically limited excursion (e.g. bottoming, spider crash).